

LIST OF CONTENTS

CHAPTER	CONTENT	PAGE
	CERTIFICATION OF NOTES	ii
	CERTIFICATION BY SUPERVISOR	iii
	TITLE PAGE	iv
	AUTHOR'S DECLARATION	v
	DEDICATION	vi
	ACKNOWLEDGEMENTS	vii
	ABSTRACT	viii
	ABSTRAK	ix
	LIST OF CONTENTS	x
	LIST OF TABLES	xiii
	LIST OF FIGURES	xv
	LIST OF ABBREVIATIONS AND SYMBOLS	xvii
1	INTRODUCTION	1
	1.1 Introduction	1
	1.2 Aim and Objectives of Research	3
	1.3 Significance of the Research	3
	1.4 Scope of the Research	3

2	LITERATURE REVIEW	4
2.1	Introduction	4
2.2	Laterite Distribution in the World	5
2.3	Laterite Distribution in West Malaysia	6
2.4	General Information of Aggregate	6
2.5	Properties of Concrete Influenced by Aggregate Properties	7
2.5.1	Particle Shape	8
2.5.2	Particle Surface Texture	9
2.5.3	Bond and Strength of Aggregate	10
2.5.4	Coarse Aggregate	11
3	RESEARCH METHODOLOGY	12
3.1	Introduction	12
3.2	Selection of Material	13
3.2.1	Cement	13
3.2.2	Supplementary Cementitious Materials	13
3.2.2.1	Silica fume	14
3.2.2.2	GGBF Slag	16
3.2.3	Coarse Aggregate	18
3.2.4	Fine Aggregate	20
3.2.5	Water	20
3.3	Tests on Aggregate	21
3.3.1	Sieve Analysis Test	21
3.3.2	Aggregate Crushing Value	22
3.3.3	Flakiness and Elongation Index Test	23
3.4	Mix Proportions and Details of Samples	25
3.5	Measurement of Workability by Slump Test	26
3.6	Curing	27
3.7	Tests on Hardened Concrete	28

	3.7.1 Compressive Strength Test	28
	3.7.2 Flexural Strength Test	29
	3.7.3 Equivalent Cube Test	30
	3.7.4 Splitting Tensile Strength Test	31
	3.7.5 Ultrasonic Pulse Velocity Test	32
4	RESULTS AND DISCUSSION	34
	4.1 Introduction	34
	4.2 Coarse Aggregate Tests Results	35
	4.2.1 Sieve Analysis Test Results	35
	4.2.2 Elongation and Flakiness Index Test Result	38
	4.2.3 Aggregate Crushing Value Test Results	40
	4.3 Slump Test Result	41
	4.4 Compressive Strength Result	42
	4.5 Flexural Strength Results	45
	4.6 Modified Compressive Strength Test Results	47
	4.7 Splitting Tensile Strength Results	47
	4.8 Ultrasonic Pulse Velocity Test Results	48
5	CONCLUSION AND FUTURE WORK	51
	5.1 Introduction	51
	5.2 Conclusions	52
	5.3 Recommendations	53
	REFERENCES	54

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Properties of concrete influenced by aggregate properties	7-8
2.2	Particle shape classification of BS 812: Part 1: 1975 with Examples	9
2.3	Surface texture of aggregates	10
2.4	Compressive strength of test samples at different ages	11
3.1	General properties and specifications of silica fume	16
3.2	Chemical analysis of GGBF slag	18
3.3	Sieve sizes used in this study according to BS 812: Part 103.1: 1985	22
3.4	Quantities of the constituents per cubic meter	25
3.5	The tests, number of specimens for every age	26
4.1	Results of sieve analysis of crushed granite aggregate	35
4.2	Results of sieve analysis of laterite aggregate	36
4.3	Results of elongation and flakiness index of crushed granite and laterite aggregate	38
4.4	Percentage of elongation and flakiness index	38
4.5	Aggregate crushing value (ACV) test results	40
4.6	Compressive strength results	43
4.7	Flexural strength results	46
4.8	Comparison between cube (1) and modified (2) compressive strength results	47
4.9	Splitting tensile strength results (MPa)	48

4.10	Relationship between Compressive strength and pulse velocity	50
4.11	Relationship between flexural strength and pulse velocity	50

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
1.1	Laterite aggregate	2
2.1	Distribution of the earth's eight major terrestrial of biomes	5
3.1	Silica fume	15
3.2	GGBF Slag	17
3.3	Coarse aggregate	19
3.4	Crushed granite aggregate replaced with 25% laterite aggregate	19
3.5	Fine aggregate used in the study	20
3.6	Standard apertures	22
3.7	Cylindrical mould and a plunger used in ACV test	23
3.8	Metal length gauge	24
3.9	Metal thickness gauge	24
3.10	Slump test procedure	27
3.11	Compressive strength test	29
3.12	Flexural strength test	30
3.13	Modified compressive strength test	31
3.14	Splitting tensile strength test	32

3.15	Ultrasonic pulse velocity equipment	33
4.1	Grading graph of laterite and crushed granite aggregate	37
4.2	Slump test result	41
4.3	Compressive strength results for different mixes	43
4.4	Mode of failure of laterite concrete and crushed granite concrete	44
4.5	Flexural strength result for different mixes	46
4.6	Relationship between compressive strength and pulse velocity	49
4.7	Relationship between flexural strength and pulse velocity	50

LIST OF ABBREVIATIONS AND SYMBOLS

Abbreviations:

BS	=	British Standard
ASTM	=	American Society for Testing and Materials
DOE	=	Department of Environment
SF	=	Silica Fume
GGBFS	=	Ground Granulated Blast furnace Slag

Symbols:

SiO_2	=	Silicon Oxide
Fe_2O_3	=	Ferric Oxide
Al_2O_3	=	Aluminum Oxide
$\text{Ca}(\text{OH})_2$	=	Calcium Hydroxide
C-S-H	=	Calcium Silicate Hydrate